



Plan View
Scale 1" = 40'

NOTES

1. Refer to luminaire schedule for total LLF.
2. Please refer to the "luminaire locations" table for mounting heights.
3. Product information can be obtained at www.Lithonia.com or through your local agency.
4. Approx spacing is 130' x 171' to achieve 0.5fc

LUMINAIRE LOCATIONS				
No.	Label	MH	Orientation	Tilt
1	A	30.0	90.0	0.0
2	A	30.0	90.0	0.0
3	A	30.0	90.0	0.0
4	A	30.0	90.0	0.0
5	A	30.0	90.0	0.0
6	A	30.0	90.0	0.0

STATISTICS						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Typical Parking Summary	+	2.0 fc	6.5 fc	0.6 fc	10.8:1	3.3:1

LUMINAIRE SCHEDULE									
Symbol	Label	Qty	Catalog Number	Description	Lamp	File	Lumens	LLF	Watts
■	A	6	AS2 400M SR4W (PULSE START)	ARCHITECTURAL ARM-MOUNTED CUTOFF LUMINAIRE WITH SR4W REFLECTOR. MEETS THE 'NIGHTTIME FRIENDLY' CRITERIA	ONE 400 WATT CLEAR ED28 PULSE START METAL HALIDE IN HORIZONTAL POSITION	AS2_400M_SR4W_(PULSE_START).ies	38000	0.72	912