

*IF DAYLIGHTING IS REQUIRED, ADDITIONAL RELAY PACK(S) MAY ALSO BE REQUIRED.

SEQUENCE OF OPERATION:


LIGHTS
- ALL LIGHTS ARE DIMMABLE
- EACH ROW/FIXTURE CONTROLLED INDEPENDENTLY
- MAXIMUM LEVEL CAN BE LIMITED TO 80%

OCCUPANCY
- LIGHTS MUST BE TURNED ON MANUALLY (OR CAN BE RECONFIGURED TO BE AUTO ON TO 50%)
- LIGHTS AUTOMATICALLY TURN OFF WHEN ROOM BECOMES VACANT

DAYLIGHT
- SMOOTH CONTINUOUS DIMMING
- DAYLIGHT ZONES DEFINED BY ROWS (OR CUSTOM GROUPING OF FIXTURES)
- NOT REQUIRED IN SPACES WITHOUT SIDE LIT AREAS < 250FT²

MANUAL
- ON/OFF & RAISE/LOWER CONTROL OF TWO GROUPS OF LIGHTS

ADDITIONAL OPTIONS:
- SURFACE OR RECESSED MOUNT SENSORS ALSO AVAILABLE
- ADD nPODM 4S FOR FOUR SCENE OR nPODM GFX FOR TOUCH SCREEN CONTROL
- ROOM CAN BE CONNECTED TO NLIGHT BACKBONE TO ENABLE NETWORK CONTROL INCLUDING TIME BASED CONTROLS AND INTEGRATION WITH BUILDING MANAGEMENT SYSTEMS.
- FOR EMERGENCY LIGHTING CONTROL, ORDER FIXTURES WITH -n80EMG OR n100EMG OPTION



BILL OF MATERIAL		
QTY	PRODUCT #	DESCRIPTION
6	VARIES	nLIGHT ENABLED FIXTURE
1	nCM PDT 9	DUAL TECHNOLOGY OCCUPANCY SENSOR
1	nPODM DX	ON/OFF & RAISE/LOWER WALL POD
OPTIONS		
1	nCM ADCX	AUTOMATIC DIMMING CONTROL PHOTOCELL
1	nPP20 PL	PLUG LOAD RELAY PACK

SUPPORTS THE FOLLOWING REQUIREMENTS:

✓ FULL AUTO-OFF VIA OCCUPANCY SENSOR

✓ LOCAL SWITCH

✓ MULTI-LEVEL/ DIMMING CONTROL

✓ MULTI-LEVEL DAYLIGHT CONTROL