

CUSTOM COLOR SUBMITTAL FORM- REQUESTOR MAIL TO CUSTOM COLOR CONTACT (CCC) IN SECTION 3

Please Read through and complete all lines. Agent questions reach out to Acuity CR. Customer questions reach out to Agent.

Today's Date	
Quote or Order Number	
Date Needed	
Project name	
If yes, paint vendor name	
If yes, their part number	

If this is a request for Vitraccoat match please answer the below questions

Is this a pole?	yes	no		
Is fixture for match installed inside or outside?	Inside	Outside		
Is it withn 50 mles of salt water?	yes	no		
Finish of matching sample chip?	smooth	textured	same as chip	
Gloss level of matching sample chip?	matte	semi gloss	gloss	same as chip

For Sherwin Williams match request Sherwin Williams use PO 1479324, and a DTM water base paint for matching. Ship to contact in Section 2 and 3 below using UPS account 384522

**REQUESTOR-PLEASE COMPLETE SECTION 1 & 2 AND ABOVE. WHEN COMPLETE MAIL TO CCC IN SECTION 3
PAINT SUPPLIER- PLEASE MAIL A MATCHING SAMPLE CHIP TO PERSON IN SECTION 2 AND 3**

1 Requestor submitting form (Agent)

1	Requestor Name:	
	Company:	
	Address:	
	City, State & zip code :	Phone: ()

2 Name and address of person to approve sample chip

IF NO AUTHORIZATION NEEDED TO APPROVE MATCHING SAMPLE CHIP REQUESTOR INITIAL AND DATE BOX TO RIGHT

2	Name:	
	Company:	
	Address:	
	City, State & zip code :	Phone: ()

3. CCC Contact for return of matching sample chip for safe keeping

3	Company:	Acuity Brands Lighting
	c/o	c/o Mary Scagnelli
	Address:	37 Fair Oaks Dr. SE
	City, State & zip code :	Conyers, GA 30094

**Vitracoat Lab Work
Request to be
completed by
Vitracoat**

CUSTOMER:	Acuity Brands Lighting	LAB #	
REP NAME:	Hector Citron	DATE:	
REQUEST:	Match	DATE NEEDED:	
POWDER MANADATORY?	yes	no	
COLOR NAME:			
USAGE (lbs/year):	n/a		
STANDARD:	Competitor's Panel		
CHEMISTRY:	Polyester TGIC		
FINISH:	Same as panel or powder		
SUBSTRATE:	CR		
PRETREATMENT:	Zinc Ph		
APPLICATION METHOD:	Corona		
APPLICATION MODE:	Spray-to-Waste		
LIGHT:	D65 (Day Light)		
BAKE CYCLE:		Time (min):	Over Set (°F):
		Dwell Time (min):	Part Temp (°F):
FILM THICKNESS (mil):	2.0-3.0	ANGLE:	60
SALT SPRAY (HOURS):	500	FLEXIBILITY:	32%
IMPACT (lb/in):	120	QUV(HOURS):	500
ENCLOSED:	Panel	HARDNESS:	2H
SEND:	Powder (lbs):	5	Panels: 5

Panel, MSDS and First Piece Report are always sent.

NOTES: