

**SEQUENCE OF OPERATION:**

**LIGHTS**

- ALL LIGHTS ARE DIMMABLE
- EACH FIXTURE INDEPENDENTLY CONTROLLED
- MAXIMUM LEVEL CAN BE LIMITED TO 80%
- OPTIONAL AUTOMATIC LUMEN COMPENSATION

**OCCUPANCY**

- LIGHTS AUTOMATICALLY GO TO FULL BRIGHT WHEN OCCUPIED
- LIGHTS AUTOMATICALLY TURN OFF WHEN SPACE BECOMES VACANT

**DAYLIGHT**


- SMOOTH CONTINUOUS DIMMING
- CUSTOM GROUPING OF FIXTURES INTO SEPARATE DAYLIGHT ZONES (MAX. NUMBER OF ZONES = NUMBER OF FIXTURES)
- NOT REQUIRED FOR SPACES WITHOUT WINDOWS OR SIDE LIT AREAS < 150W LOAD

**MANUAL**

- MASTER ON/OFF & RAISE/LOWER CONTROL OF ENTIRE SPACE (NOT REQUIRED)


**ADDITIONAL OPTIONS:**

- SURFACE OR RECESSED MOUNT SENSORS ALSO AVAILABLE
- SPACE/ ZONE CAN BE CONNECTED TO nLIGHT BACKBONE TO ENABLE NETWORK CONTROL INCLUDING TIME BASED CONTROLS AND INTEGRATION WITH BUILDING MANAGEMENT SYSTEMS.



BILL OF MATERIAL		
QTY	PRODUCT #	DESCRIPTION
5	SEE NOTE	nLIGHT AIR ENABLED FIXTURES
1	rPODB DX G2	ON/OFF & RAISE/LOWER WALL POD

**SUPPORTS THE FOLLOWING REQUIREMENTS:**



**Note:** Contact your local lighting agent for more information on nLight enabled fixtures