



**SEQUENCE OF OPERATION:**

LIGHTS

- ALL LIGHTS ARE DIMMABLE
- MAXIMUM LEVEL CAN BE LIMITED TO 80%

OCCUPANCY

- LIGHTS AUTOMATICALLY GO TO FULL BRIGHT WHEN OCCUPIED
- LIGHTS AUTOMATICALLY DROP TO 50% (OR OTHER DIM SETTING) WHEN SPACE BECOMES VACANT

MANUAL

- NOT REQUIRED

ADDITIONAL OPTIONS:

- SURFACE OR RECESSED MOUNT SENSORS ALSO AVAILABLE
- SPACE / ZONE CAN BE CONNECTED TO nLIGHT BACKBONE TO ENABLE NETWORK CONTROL OR ADR (AUTOMATIC DEMAND RESPONSE)
- HVAC CONTROL AVAILABLE THROUGH SYSTEM-WIDE BACNET INTERFACE OPTION ON ECLYPSE CONTROLLER.

① Fixtures assumed to be battery backup

DIAGRAM LEGEND	
	LINE FEED

BILL OF MATERIAL		
QTY	PRODUCT #	DESCRIPTION
1	SEE NOTE	nLIGHT AIR ENABLED FIXTURES
1	SEE NOTE	nLIGHT AIR ENABLED FIXTURES (BATTERY BACKUP)

**SUPPORTS THE FOLLOWING REQUIREMENTS:**



PARTIAL / AUTO-OFF VIA OCCUPANCY SENSOR



TIME SCHEDULE READY WITH NETWORKED LIGHTING SYSTEM (nGWY 2)



MULTI-LEVEL/ DIMMING CONTROL

**Note:** Contact your local lighting agent for more information on nLight enabled fixtures