

SEQUENCE OF OPERATION:

LIGHTS

- ALL LIGHTS ARE DIMMABLE
- MAXIMUM LEVEL CAN BE TASK TUNED TO ANY PERCENTAGE VIA PROGRAMMING

OCCUPANCY

- LIGHTS AUTOMATICALLY GO TO FULL BRIGHT WHEN OCCUPIED
- LIGHTS AUTOMATICALLY TURN OFF WHEN SPACE BECOMES VACANT OR CONFIGURED TO DROP TO LOW DIM SETTING

DAYLIGHT

- DAYLIGHT RESPONSIVE CONTROLS LIGHTS TO FULL OFF WHEN ADEQUATE DAYLIGHT PRESENT
- NOT REQUIRED FOR SPACES WITHOUT SKYLIGHTS OR LOADS <150W IN TOPLIT ZONES

MANUAL

- MASTER ON/OFF & RAISE/LOWER CONTROL OF ENTIRE SPACE


ADDITIONAL OPTIONS:

- SPACE / ZONE CAN BE CONNECTED TO nLIGHT BACKBONE TO ENABLE NETWORK CONTROL INCLUDING TIME BASED CONTROLS AND INTEGRATION WITH BUILDING MANAGEMENT SYSTEMS.

DIAGRAM LEGEND	
	LINE VOLTAGE WIRES
	EM LINE VOLTAGE WIRES
	LINE FEED
	EM LINE FEED

BILL OF MATERIAL		
QTY	PRODUCT #	DESCRIPTION
20	SEE NOTE	nLIGHT AIR ENABLED FIXTURE
15	SEE NOTE	nLIGHT AIR ENABLED FIXTURE WITH EM OPTION
3	rPODB 2P G2	2-POLE ON/OFF WALL POD

SUPPORTS THE FOLLOWING REQUIREMENTS:



Note: Contact your local lighting agent for more information on nLight enabled fixtures