



SEQUENCE OF OPERATION:

LIGHTS

- SWITCHING ONLY, NO DIMMING

OCCUPANCY

- LIGHTS AUTOMATICALLY TURN ON WHEN OCCUPANT ENTERS
- LIGHTS AUTOMATICALLY TURN OFF WHEN SPACE BECOMES VACANT

MANUAL

- MASTER ON/OFF CONTROL OF ENTIRE SPACE

ADDITIONAL OPTIONS:

- SURFACE OR RECESSED MOUNT SENSORS ALSO AVAILABLE
- SPACE CAN BE CONNECTED TO NLIGHT BACKBONE TO ENABLE NET-WORK CONTROL OR TIME SCHEDULES (C405.2.2)
- FOR EMERGENCY LIGHTING CONTROL ADD A NPP16 D ER PACK.

DIAGRAM LEGEND

CAT-5e CABLE

LINE VOLTAGE WIRES

LINE FEED

BILL OF MATERIAL

QTY	PRODUCT #	DESCRIPTION
1	nPP16	RELAY PACK
1	nWSX PDT LV	DUAL TECHNOLOGY OCCUPANCY WALL SWITCH

SUPPORTS THE FOLLOWING REQUIREMENTS:

FULL AUTO-OFF VIA OCCUPANCY SENSOR (C405.2.1.1)

LOCAL SWITCH (C405.2.2.3)